

Model	V1210
Description	2x 2.5G Network Port Fanless Appliance
Processor	Intel® N5105 (64 Bit, 2.0GHz, Turbo 2.9GHz, 4M L3 Cache)
Processor Cores	4
Processor Threads	4
Intel AES-NI	Supported
Virtualization	Intel Vt-x, Vt-d
Network	2x Intel I226-V 2.5G Ethernet, RJ-45
Video / Graphics	Intel UHD Graphics, 1x HDMI 1.4
Audio	Audio over HDMI
Memory	1x 4GB LPDDR4-2933, Soldered
Storage	1x M.2 2280 NVMe, 1x 32G eMMC on board
Optional Storage	None
External I/O	2x RJ-45 Ethernet
	4x USB 3.0 Type A
	1x USB Type C Console
	1x HDMI
	Reset Button (Recessed), GPIO
	6x WiFi/LTE Antenna Mounting Holes
	1x 12V DC Power Jack, Screw in connector
Internal I/O	1x M.2 2280 M-Key PCIe 3.0 x1 (NVMe)
	1x M.2 2280 E-Key PCIe 3.0 x1 (WiFi)
	1x M.2 3052 B-Key PCIe 3.0 x1 or USB 3.0 (LTE)
	1x CMOS Reset (3 pin)
BIOS	AMI, coreboot TBD
Indicators	1x LED Power Button (Blue), 1x LED Power Indicator (Green), 1x LED Disk Activity Indicator (Red)
Power	Input 12V DC, 1x DC Power Jack, Screw in connector
Power Usage	Max 24W
Chassis	Fanless, Aluminum, Black
Chassis Dimensions	4.5 x 4.5 x 2 in, 115 x 115 x 50 mm
Mounting Options	Desktop, Optional VESA Bracket, Optional 1RU Rack Mount
Weight	1 lb, .45 Kg
Shipping Weight	3 lbs 4 oz, 1.47 Kg
Operating Temperature	+14° - +122° F, -10° - +50° C
Operating Humidity	0 – 95% relative humidity, non-condensing
Approvals	UL (Power Supply), FCC Part 15 Class B, CE, RoHS
Country of Origin	Made in China, Assembled in USA, Canada, or Germany
Optional Connectivity	1x WiFi, 1x LTE